

63xx series Quick start Guide

(Argon Audio 6340, 6350, 6344C, 6344FS and 6355FS)

We care about the Environment

By refraining from inserting a full printed manual with our Argon Audio products we save more than 20 tons of paper each year. You can find full product information for this product on; www.argonaudio.com

Speaker positioning

The Speakers are best used with the tweeters approximately at ear level when seated. Variations in placement of your Speakers can produce dramatic differences in the way music sounds. No listening rooms are the same and therefore we encourage you to spend some time experimenting with which placements work best in your listening room. Trust your ears and be willing to experiment freely. You can start with our basic recommendations.

Please try to ensure that the rooms surroundings of each Speaker left and right are similar in acoustic character. For example, if one Speaker is placed on bare walls while the other is placed close to soft furniture's and curtains, both the overall sound quality and the stereo image are likely to be compromised. Because bookshelves are usually located close to the wall, placement on bookshelves will often provide a richer, more full-bodied sound. In other words; you will get more Bass. On the other hand, if you place the Speakers free-standing You will get less Bass but a clearer sound. To begin with, the Speakers should be positioned between 1.5m and 3m apart at two corners of an equilateral triangle completed by the listening area at the third corner. See fig. 1

Home Theatre Systems

Argon Audio 63xx series speakers can be used as front channels in a surround sound home theatre system. Positioning the front Speakers within approximately 1metre of the sides of your TV will create the best sound image in scale with the visual image. The Speakers' height should ideally be between the centre and top of the screen. If the Speakers are to be used for reproducing the surround channels in a multi channel home theatre system, we suggest you place them as illustrated in Figures 2 to 4 depending on the number of channels.

Connecting your loudspeakers

We recommend that you read the manual of your amplifier or AV-receiver carefully before connecting your Speakers. Please switch off all equipment when connecting your Speakers. The binding posts on the terminal accepts wire up to Ø 4mm or cables with banana plugs. Make sure that positive terminal binding posts on the Speaker (marked + and colored red) are connected to the positive output terminal binding posts on the amplifier and that the negative terminals on the Speaker (marked – and colored black) are connected to the negative output terminal on the amplifier. See fig 5.

You are now ready to enjoy your Argon Audio Speakers...!

Running-in period

We recommend a running-in time of your Argon Audio Speakers of approximately 15-20 hours at normal listening level before you decide on the final positioning of the Speakers. During the running-in time the drive units will settle in and perform as intended.

fig. 1 stereo




fig. 2 surround 5.1




fig. 3 surround 6.1




fig. 4 surround 7.1




fig. 5 amplifier & terminal

